

Technical Data Sheet

SM 6000

Page 1 / 2

1. Product Name and Description

Spray Lubricant SM 6000.

The product is used for rust prevention and lubrication of machinery and the parts.

2. Features

- _ Excellent rust prevention.
- _ Outstanding lubrication
- _ Excellent penetration into narrow gaps.
- _ Easy and effective way to use with extension nozzle.

3. Applications

- Stops squeaks
- Cleans and protects from rusting.
- Loosens rusted parts
- Softens sticky mechanism
- Drives out moisture

4. Technical Data

▶ Physical state	Creamier colored liquid
▶ Specific gravity	0.823
▶ Application temperature [°C]	+5 and +40
▶ Temperature resistance [°C]	-10 and +80
▶ Freeze point(@40°C)	5.27cSt
▶ Viscosity (25°C) [cPs]	30±3
▶ Nonvolatile Content of Varnishes [%](ASTM D-1644-75)	45
▶ Dielectric strength (ASTM D-87749)	38kV/2.54mm
▶ Average thickness of film	3~5μ
▶ Applying amount	70~80m ² /can
▶ Corrosion Standards and Wear Standards (ASTM B-117)	120hr



1001 DGV 290-2 Gocheon-dong Euiwang-si Kyunggi-do, Korea

(T)+82-31-450-6633 (F)+82-31-450-6630

www.nurichem.com nurichem@nurichem.com

Technical Data Sheet

SM 6000

Page 2 / 2

5. Packaging

360 ml/can, 24 can/ carton box

6. Shelf life

24 months if stored upright between + 5 and + 25°C.

7. How to use:

- Spraying after cleaning foreign substances is more effective
- To clean rust and various foreign substances, clean it with wiper or brush after some time passes after spraying.
- Spray it sufficiently to keep lubricating and anti-rusting film even.
- Spray with extension tube to the non-accessible areas.

8. Cautions

- Do not use near heater or stove
- Do not use in the room using fire
- Do not keep it in the place above 40°C
- Provide ventilation when used in the closed room
- Do not throw it away into fire
- Punch can before throwing it away



1001 DGV 290-2 Gocheon-dong Euiwang-si Kyunggi-do, Korea

(T)+82-31-450-6633 (F)+82-31-450-6630

www.nurichem.com nurichem@nurichem.com